



NGA-504

Addressable Wall Mount Sounder/ Beacon

NGA-504 is a Wall Mounted Addressable Sounder/ Beacon with low power consumption. Up to 32 individually addressed sounders can be installed per loop occupying address 94 to 125. The address is set using switches 1 to 5 of the 8 way DIL switch. Four different tones are available and selected using DIL switches 6 and 7.

When individual address reporting is not required, NGA-504 can be configured as a Shadow Sounder. In this case sounders do not occupy an address in the loop thus freeing up addresses for more detection devices. Shadow sounders do not report back to the control panel so their presence on the loop is not monitored. Shadow sounders draw current from the loop (4.1 mA in alarm) and must be included in loop load calculations.

Specifications

SUPPLY VOLTAGE	Loop: 17 V to 30 V DC
LOOP CURRENT - QUIESCENT	0.5 mA
LOOP CURRENT - ALARM LOW FREQ.	4.1 mA (Max.) - 2.6 mA (Min.)
LOOP CURRENT - ALARM HIGH FREQ.	7.5 mA (Max.) - 3 mA (Min.)
LOOP CURRENT - ALARM BEACON	1.4 mA
SOUNDER OUTPUT - CONTINUOUS	102 dB @ 1 m (Max.) - 97 dB @ 1 m (Min.)
SOUNDER OUTPUT - LOW FREQ.	103 dB @ 1 m (Max.) - 98 dB @ 1 m (Min.)
SOUNDER OUTPUT - HIGH FREQ.	110 dB @ 1 m (Max.) - 100 dB @ 1 m (Min.)
MAX. CABLE SIZE	2.5 mm ²
MAX. HUMIDITY	95% RH Non-Condensing
OPERATING TEMPERATURE	0°C to 50°C
ENCLOSURE - MATERIAL	Red / White ABS
PROTECTION CATEGORY	IP44
DIMENSIONS	110 (Dia) x 85.1 (H) mm
WEIGHT	254 g - including mounting base

Ordering Information

NGA-504	Addressable Sounder
NGA-505	Addressable Sounder/Beacon